


Tunable Band Reject Filter Inspection Report

67-4313-01 REV -
TTR3000-3EE
SHT 2

TEST LEVEL				TEST POINT	TEST PARAMETER	LIMIT / UNIT	Serial Number:						
			X	Fc	NOTCH FREQUENCY	MHz	2000	3000	4000				
			X	Fc	ATTENUATION	40 dB MIN.							
			X	Fc	40 dB BANDWIDTH	20 kHz MIN.							
			X	VSWR 1.5 / 1	UPPER LIMIT	MHz							
			X	VSWR 1.5 / 1	LOWER LIMIT	MHz							
			X	VSWR 1.5 / 1	BANDWIDTH	190 MHz MAX.	0.00	0.00	0.00				
			X	VSWR 1.5 / 1	PASSBAND	1.5 / 1	a	a	a				
			X	Fc + 80 MHz	INSERTION LOSS	1.0 dB MAX.							
			X	Fc - 80 MHz	INSERTION LOSS	1.0 dB MAX.							
			X	Fc	DIAL ERROR	+/- 1% MAX	a	a	a				
F.A.	1 / LOT	100%	GOV'T SOURCE INSPECTION				TELONIC ACCEPTANCE			DATE			
			Req'd	YES	C	Stamp	Insp.		Date		Tech.		
TELONIC MODEL NO.						Tunable Band Reject Filter							
TTR3000-5EE						* Where VSWR within Notch exceeds 1.5/1							
TELONIC DRAWING NO.			REV.	WORK ORDER NO.									
67-4313-01			-										
CUSTOMER DRAWING NO.			REV.	ENGR.	DATE								
				RG	7/25/2012								